



为您的产品保驾护航

PRODUCT DATASHEET

Electro-Static Discharge

JED323-5V-LG ESD


## Features

- Package: SOD-323
- 360W peak pulse power (8/20 $\mu$ s)
- Ultra low capacitance: 1pF typical
- Ultra low leakage: nA level
- Operating voltage: 5V
- Low clamping voltage
- Protects one power line or data line
- Complies with following standards:
  - IEC 61000-4-2 (ESD) immunity test
    - Air discharge:  $\pm 30$ kV
    - Contact discharge:  $\pm 30$ kV
  - IEC61000-4-5 (Lightning) 18A (8/20 $\mu$ s)
- RoHS compliant

## Applications

- USB Ports
- Smart Phones
- Wireless Systems
- Ethernet 10/100/1000 Base T

## Schematic Diagram



## Pin Description




## Limiting Values( $T_A = 25^\circ\text{C}$ , unless otherwise specified)

Symbol	Parameter	Conditions	Value	Unit
$V_{ESD}$	Electrostatic Discharge Voltage	IEC 61000-4-2;Contact Discharge	$\pm 30$	kV
		IEC 61000-4-2;Air Discharge	$\pm 30$	kV
$P_{PP}$	Peak Pulse Power	$t_P=8/20\mu s$	360	W
$I_{PP}$	Peak Pulse Current	$t_P=8/20\mu s$	18	A
$T_J$	Operating Temperature Range	-	-55 to +125	$^\circ\text{C}$
$T_{stg}$	Storage Temperature Range	-	-55 to +150	$^\circ\text{C}$


## Electrical Characteristics( $T_A = 25^\circ\text{C}$ , unless otherwise specified)

Symbol	Parameter	Conditions	Min	Typ.	Max	Unit
$V_{RWM}$	Reverse Working Voltage	$T_A=25^\circ\text{C}$	-	-	5	V
$V_{BR}$	Breakdown Voltage	$I_T=1\text{mA}$	6	-	-	V
$I_R$	Reverse Leakage Current	$V_{RWM}=5\text{V}; T_A=25^\circ\text{C}$	-	-	0.2	$\mu\text{A}$
$V_C$	Clamping Voltage	$I_{PP}=1\text{A}(8 \times 20\mu s \text{ pulse})$	-	-	10	V
$V_C$	Clamping Voltage	$I_{PP}=18\text{A}(8 \times 20\mu s \text{ pulse})$	-	-	20	V
$C_J$	Junction Capacitance	$V_R=0\text{V}, f=1 \text{ MHz}$	-	1	-	pF


Typical Characteristics




Junction Capacitance vs. Reverse Voltage




Peak Pulse Power vs. Pulse Time




Clamping Voltage vs. Peak Pulse Current (tp = 8/20 μs)



Power Derating Curve




8 X 20 μs Pulse Waveform




ESD Clamping Voltage  
8 kV Contact per IEC61000-4-2

Physical Dimensions(mm.)



Symbol	Dimensions In Millimeters		
	Min	Nom	Max
A	0.800	--	1.100
A1	0.800	--	0.900
A2	0.000	--	0.100
b	0.250	--	0.400
c	0.080	--	0.177
D1	1.600	1.700	1.800
D	2.300	--	2.800
E	1.150	--	1.400
L	0.475REF		
L1	0.100	--	0.500
e	0°	--	8°

Suggested Land Pattern




Unit:mm

Packaging Quantity

Part Number	Delivery Form	Delivery Quantity
JED323-5V-LC	7"T&R	3,000

### Soldering Parameters



Reflow Condition		Pb-Free Assembly
Pre-heat	-Temperature Min( $T_{s(min)}$ )	+150°C
	-Temperature Max( $T_{s(max)}$ )	+200°C
	-Time(Min to Max)( $t_s$ )	60~180 secs.
Average ramp up rate (Liquid us Temp( $T_L$ ) to peak)		3°C/sec. Max
Ts(max) to $T_L$ - Ramp-up Rate		3°C/sec. Max
Reflow	-Temperature( $T_L$ )(Liquid us)	+217°C
	-Temperature ( $t_L$ )	60~150 secs.
Peak Temp ( $T_P$ )		+260(+0/-5)°C
Time within 5°C of actual Peak Temp ( $t_p$ )		30 secs. Max
Ramp-down Rate		6°C/sec. Max
xTime 25°C to Peak Temp (TP)		8 min. Max
Do not exceed		+260°C

### Part Number System

## JE D323 - 5V - L C

